

## DESCRIPTION

Sub 3  
a >SEMICONDUCTOR DEVICE PROVIDED WITH LOW MELTING POINT METAL

Ins. a' &gt;

BUMPS AND PROCESS FOR PRODUCING SAME

5

Technical Field

The present invention relates to a semiconductor device provided with low melting point metal bumps and a process for producing the same.

## 10 Background Art

Semiconductor devices have currently been used widely in various fields. The semiconductor devices are usually used by mounting them on substrates. The mounting methods include bonding methods such as tape automated bonding (TAB), wire bonding and flip chip bonding.

15

The TAB and wire bonding are technologies by which a semiconductor device is mounted on a substrate through leads. The leads are arranged in one row per peripheral side of the semiconductor device. The technologies are, therefore, not suited to high density mounting of the semiconductor devices. In contrast to the technologies mentioned above, flip chip bonding is a technology by which the electrodes of a semiconductor device are directly connected to the electrode terminals on the substrate through a bonding metal. Since the electrodes of the semiconductor device can be provided in a lattice-like form on the entire surface, the technology is suited to high density mounting. Various solders are generally used as bonding metal in flip chip bonding because the bonding is conducted by melting at low temperature.

20

25

30

In flip chip bonding, semiconductor devices provided with low melting point metal bumps for bonding placed on electrodes are used, and the semiconductor devices are connected to the electrode terminals of substrates by a reflowing procedure by which the bumps are melted and solidified again.

35

In general, the bumps are formed by vapor deposition or plating. However, such bump formation methods must all repeat complicated treatments steps using a mask.

Moreover, in the method of forming the bumps by vapor  
5 deposition, a bump material is deposited on portions where the bumps are not to be formed, and the deposition amount thereon is very large. The method is, therefore, not a preferred one in view of the cost and efficiency.

Moreover, wet plating such as electroplating or  
10 electroless plating fouls wafers and causes an environmental problem, and countermeasures against such problems are indispensable. As illustrated above, conventional methods for forming the bumps are relatively costly, and practical use of the methods is restricted.

15 There is a stud bump procedure as a method for forming bumps other than vapor deposition and plating. Since bumps are formed one by one in the procedure, the production efficiency is low, and in addition the bump amount tends to vary among the bumps. Accordingly,  
20 securing uniformity in bonding the semiconductor devices and the substrates is difficult.

#### Disclosure of the Invention

An object of the present invention is to provide a  
25 semiconductor device provided with low melting point metal bumps of high quality and capable of being mounted on a substrate by flip chip bonding, and a process for producing the same.

The semiconductor device of the present invention  
30 comprises electrodes formed on a semiconductor chip, and is provided with bumps each consisting of a low melting point metal ball which is spherically formed and has a given size, and adhesive bonded to the electrodes.

The low melting point metal balls are preferably  
35 adhesive bonded to the respective electrodes with a flux.

The electrodes on the semiconductor chip are preferably formed from an electrode material of Cu or a Cu alloy, Al or an Al alloy, or Au or a Au alloy.

5 When the electrode material is Al or an Al alloy, at least one layer of a metal or a metal alloy having a melting point higher than the electrode material is preferably laminated to the layer formed from the electrode material.

10 The laminated layers are preferably formed from a metal selected from Ti, W, Ni, Cr, Au, Pd, Cu, Pt, Ag, Sn and Pb, or an alloy of these metals.

15 It is preferred that, of the layers laminated to the electrode material layer, the layer contacted with the electrode material layer be formed from Ti, W, Ni, Cr, Pd, Cu or Pt, or an alloy of these metals, and that the layer contacted with the low melting point metal ball be formed from Ni, Au, Pd, Cu, Pt, Ag, Sn or Pb, or an alloy of these metals.

20 The process for producing a semiconductor device according to the present invention is a process for producing a semiconductor device having electrodes formed on a semiconductor chip, and provided with bumps which consist of low melting point metal balls each being formed spherically and having a given size, and which are  
25 adhesive bonded to the respective electrodes, and is characterized by the low melting point metal balls being adhesive bonded and fixed to the respective electrodes with a flux.

30 The flux is preferably applied to the electrodes.

35 On another aspect of the present invention, the process for producing a semiconductor device according to the present invention is a process for producing a semiconductor device provided with low melting point metal bumps on the electrodes on a semiconductor chip, the process comprising the steps of:

adhesive bonding low melting point metal balls each being spherically formed and having a given size to the respective electrodes, and

reflowing the low melting point metal balls.

5       The low melting point metal balls are preferably adhesive bonded to the respective electrodes with a flux. The flux is preferably applied to the electrodes.

#### Brief Description of the Drawings

10       Fig. 1 is a perspective view illustrating a semiconductor device of the present invention.

Fig. 2 is a view illustrating an electrode in the semiconductor device of the present invention.

15       Fig. 3 is a view illustrating a semispherical bump of the semiconductor device of the present invention which bump is formed by reflowing a low melting point metal ball.

20       Figs. 4A to 4D are views illustrating a process for producing the semiconductor device of the present invention.

Fig. 5 is a view illustrating a bump of a solder ball directly formed on a chip electrode of a single material.

25       Figs. 6A and 6B are views illustrating a preferred method for adhesive bonding low melting point metal balls to the respective electrodes.

#### Best Mode for Carrying Out the Invention

30       Fig. 1 shows a semiconductor device 1 of the present invention. The semiconductor device 1 is provided with low melting point metal ball bumps 3 adhesive bonded onto the electrodes (not shown) formed on a surface of a semiconductor chip 2.

35       The low melting metal balls 3 can be formed from one of the various solders used for mounting a semiconductor device on a substrate. Examples of the solders include solders of Sn alloys such as a Sn-Pb alloy and a Sn-Ag alloy and solders of Pb alloys such as a Pb-In alloy.

The electrodes to which the bumps 3 of low melting point metal balls are adhesive bonded can be formed from an electrode material of Cu or a Cu alloy, Al or an Al alloy, or Au or a Au alloy. In the semiconductor device  
5 of the present invention, an electrode having a surface area of 900 to 22,500  $\mu\text{m}^2$  is preferably used. That is, when a square electrode is used, one of the sides of the electrode has a dimension of 30 to 150  $\mu\text{m}$ .

When the electrode material is Al or an Al alloy,  
10 connecting solder balls (the term solder balls designates low melting metal balls hereinafter and is used below) to an electrode by reflowing deteriorates the bonding between the solder balls and the electrode. When Al or an Al alloy is used as an electrode material, at least one layer  
15 of a metal or an alloy of the metal having a melting point higher than the electrode material is laminated to the layer formed of the electrode material to avoid the deterioration. A typical example of the material used as the material therefor is a metal selected from Ti, W, Ni, Cr, Au, Pd, Cu, Pt, Ag, Sn and Pb, or an alloy of these  
20 metals. Of these substances, Ti, W, Ni, Cr, Pd, Cu or Pt, or an alloy of these metals is particularly effective in bonding between the material and the layer formed from Al or its alloy. Accordingly, any of the above metals or an alloy of these metals is preferably used as a layer  
25 contacted with the layer of Al or its alloy. Moreover, a solder generally shows good wettability with Ni, Au, Pd, Cu, Pt, Ag, Sn or Pb, or an alloy of these metals. Of layers laminated to the electrode material layer of Al or an Al alloy, the layer contacted with the solder ball is,  
30 therefore, preferably formed from these materials.

As explained above, when Al or an Al alloy is used, the electrode has a multilayered structure as illustrated in Fig. 2. In Fig. 2, an electrode 8 is formed as a  
35 laminated structure including a first layer 5 made of Al (or an Al alloy) on a surface of a semiconductor chip 2, a

second layer 6 made of Cr on the first layer, and a third layer 7 made of Cu on the second layer.

In addition to the laminated structure successively having from the semiconductor chip side an Al (or Al alloy) layer, a Cr layer and a Cu layer (such a laminated structure being represented as Al/Cr/Cu hereinafter) as illustrated in Fig. 2, examples of the laminated structure of the electrode in which Al or its alloy is used as an electrode material may include Al/Ni, Al/Ni/Au, Al/Ni/Cu/Au, Al/Cr/Cu/Au, Al/Ti/Cu/Au, Al/Ti/TiW (alloy)/Cu/Au, Al/TiW (alloy)/Cu/Au, Al/Cr/Ni/Pd, Al/Pd/Au, Al/Ni/Sn, Al/Cr/Cu/Pd and Al/Cr/Pt. It is needless to say that effective electrode laminated structures are not limited to the structures mentioned above in the semiconductor device of the present invention.

A flux is preferably used for adhesive bonding the solder ball to the electrode. Any of the fluxes generally used in producing semiconductor devices may be used. Although the flux may be applied to either the solder ball or the electrode surface, it is preferably applied to the electrode surface. Standard methods such as screen printing may be utilized for the method for applying the flux to the electrode surface.

When the semiconductor device of the present invention is flip chip bonded to a substrate, the solder ball bumps may be made to face the respective electrode terminals of the substrate, positioned, and contacted therewith, followed by reflowing the bumps. Such a procedure of flip chip bonding has been widely known, and it is needless to explain in detail.

The semiconductor device of the present invention may be flip chip bonded to the substrate after the solder balls are reflowed once to form semispherical bumps. Fig. 3 shows an example of a semispherical bump. The semispherical bump 10 in Fig. 3 is formed by reflowing the

solder ball bump 3 adhesive bonded to the laminated electrode 8 having been explained in Fig. 2.

In addition, the bump 10 in Fig. 3 formed by reflowing a solder ball is herein described as semispherical. The term is mainly based on the longitudinal sectional shape of the bump subsequent to reflowing as shown in Fig. 3. Electrodes on semiconductor chips have various shapes such as a circular shape, a square shape and other arbitrary shapes. For example, a bump formed by reflowing a solder ball on a square electrode has a semispherical longitudinal sectional shape as seen in Fig. 3. However, since the molten solder wets the entire square electrode surface and then solidifies, the shape viewed from above (transverse sectional shape) is not a circle but a square or a shape close to a square. Accordingly, it should be noted that the semispherical bump herein termed includes not only a bump appearing to have a circular cross sectional shape when viewed from above after reflowing but also a bump having an arbitrary transverse cross sectional shape reflecting the electrode shape under the bump. That is, "a semispherical bump" herein designates all sorts of bumps formed by reflowing solder balls adhesive bonded to electrodes having an arbitrary shape.

In order to appropriately form a semispherical bump on an electrode by reflowing a solder ball, the radius R of the solder ball to be adhesive bonded to the electrode is desirably selected so that the equation

$$0.4\sqrt{A} \leq R \leq 2\sqrt{A}$$

wherein A is the surface area of the electrode, is satisfied. When the radius R of the solder ball is less than  $0.4\sqrt{A}$ , the amount of the solder becomes insufficient, and formation of a good semispherical bump subsequent to reflowing becomes difficult. When the radius R of the solder ball exceeds  $2\sqrt{A}$ , the semispherical bump becomes large compared with the size of the electrode. Consequently, the bonded portion between the electrode and

the bump is subjected to stress concentration, and tends to be fractured.

When an electrode having a surface area of 900 to 22,500  $\mu\text{m}^2$  is used in the semiconductor device of the present invention, a preferred radius R of the solder ball derived from the above equation is from 12 to 300  $\mu\text{m}$ .

An example of the production of a semiconductor device in the present invention will be explained by making reference to Fig. 4.

As shown in Fig. 4A, a 100 x 100  $\mu\text{m}$  electrode 42 1.0  $\mu\text{m}$  thick of an Al alloy (Al-Si-Cu alloy) is formed on a semiconductor chip 41 by sputtering. The reference numeral 43 in the figure designates a passivation film which compartments the electrode thus formed. Next, a metal layer 44 of Ni and a metal layer 45 of Cu each having a thickness of 80 nm are successively laminated to the chip electrode 42 by sputtering, as shown in Fig. 4B.

What is explained above is about the step for forming a substrate on which a low melting point metal bump is to be formed. Next, as shown in Fig. 4C, a solder ball 46 of Pb-Sn alloy having a diameter of 80  $\mu\text{m}$  is adhesive bonded to the Cu metal layer 45. At the time of adhesive bonding the solder ball, the surface of the metal layer 45 is first coated with a flux (not shown) by screen printing. In cases where, for example, the solder ball placed on the electrode is subsequently to be reflowed in a reducing atmosphere, coating the metal layer 45 with the flux may be omitted. The solder ball 46 is then adhesive bonded to the flux. A preferred method for adhesive bonding the solder ball to the electrode will be explained later.

The semiconductor device of the present invention thus prepared can be flip chip bonded to a substrate by making the solder ball bumps face the respective corresponding electrode terminals of the substrate, positioning the bumps, contacting the bumps with the respective electrode terminals thereof, and reflowing the bumps.



The semiconductor device of the present invention provided with the bumps of solder balls 46 as shown in Fig. 4C may also be flip chip bonded to the substrate after forming semispherical bumps 47 by reflowing the solder balls once as shown in Fig. 4D.

5 Since an Al alloy is used as an electrode material in the above example, the Ni layer and the Cu layer are laminated to the Al alloy layer so as to firmly bond the semiconductor device to the substrate by the solder bump. 10 However, when the electrode material is neither Al nor Al alloy, for example, when the electrode material is Cu or a Cu alloy, or Au or a Au alloy, the substrate (one or more metal (or alloy) layers on the electrode material layer) for forming low melting point metal bumps is not required 15 to be formed. Accordingly, as shown in Fig. 5, a bump of a solder ball 53 can be directly formed on an electrode 52 of a semiconductor chip 51. The solder ball bump may also be reflowed once to be formed into a semispherical bump, which is thereafter used for flip chip bonding.

20 Another example will now be described, in which solder ball bumps having a diameter of 150  $\mu\text{m}$  are formed on an electrode having a diameter of 50  $\mu\text{m}$ . In this case, Cr, Cu, and Au layers are successively superposed by sputtering process on an electrode of Al-Cu alloy having a 25 diameter of 50  $\mu\text{m}$  and a thickness of 1.0  $\mu\text{m}$ , the superposed Cr, Cu, and Au layers having a thickness of 80 nm, 80 nm, and 30 nm, respectively, and a diameter which is the same as or somewhat larger than the diameter of the electrode. The surface of the Au layer is then 30 coated with a flux, on which a solder ball of Pb-Sn alloy having a diameter of 150  $\mu\text{m}$  is adhesive bonded. Shear test carried out for semispherical bumps formed by reflowing the solder balls revealed that all fractures occurred in the solder balls, and no fracture was observed 35 at the bonded portions between the bumps and electrodes.

Next, a preferred method for adhesive bonding the solder balls to the electrodes will be explained. At

present, an explanation will be made of adhesive bonding the solder balls to not electrodes each having a multilayered structure but electrodes each composed of a single material as explained in Fig. 5.

5       As shown in Fig. 6A, a vibration at a small amplitude is applied to a vessel 60 containing the solder balls 53 to cause the solder balls 53 to jump up. The solder balls 53 are then arranged and held on an arrangement base plate 63 by attracting the jumping up solder balls 53 to  
10       attraction openings 61 (attracting mechanism for attracting the solder balls being not shown) provided in the arrangement base plate 63 in positions corresponding to positions of the electrodes of the semiconductor chip to which the solder balls 53 are to be adhesive bonded.  
15       During attracting and arranging the solder balls, excess solder balls 53' adhere to portions of the arrangement base plate 63 other than the attraction openings 61, or other excess solder balls 53" adhere to the solder balls 53 attracted to the attraction openings 61, as shown in  
20       Fig. 6A. The excess solder balls 53', 53" are, therefore, removed. To achieve the removal, arbitrary procedures may be utilized. For example, excess solder balls 53', 53" can be preferably removed by applying an ultrasonic vibration to the arrangement base plate 63 in the  
25       horizontal direction. Although only two attraction openings 61 are shown in the attraction base plate 63 in Fig. 6A for the sake of simplicity, it should be noted that the actual arrangement base plate has the attraction openings the number of which is the same as that of the  
30       solder balls to be adhesive bonded to the electrodes of the semiconductor chip.

Next, as shown in Fig. 6B, the arrangement base plate 63 holding the solder balls 53 in predetermined positions is moved above the semiconductor chip 51 so that the  
35       solder balls 53 are properly positioned with respect to the respective electrodes 52 of the semiconductor chip 51. The arrangement base plate 63 is then moved downward so

that the solder balls 53 are contacted with the respective electrodes 52. After the contact, attracting the solder balls 53 to the arrangement base plate 63 is stopped (by stopping the attraction mechanism), and the arrangement  
5 base plate 63 is moved upward.

When the surface of the electrodes 52 is coated with a flux (not shown in the figure), the solder balls 53 are adhesive bonded to the electrodes due to the adhesion thereof. When the surface of the electrodes 52 is not  
10 coated with a flux, semispherical bumps adhesive bonded to the respective electrodes 52 can be formed by, for example, reflowing the solder balls 53 in a reducing atmosphere, as referred to above.

Since solder bumps can simultaneously be adhesive  
15 bonded to a large number of the respective electrodes of a semiconductor chip by the process as explained above, the process is very advantageous to the production of the semiconductor device of the present invention.

In general, a large number of semiconductor chips are  
20 formed on one wafer, and separated by cutting to give individual chips. The process as mentioned above may also be applied to a plurality of semiconductor chips prior to separation of them from the wafer by cutting, or it may be applied to individual semiconductor chips subsequently to  
25 separation of them therefrom. It is evident from what has been explained above that the semiconductor chip in the present invention includes not only a separated individual semiconductor chip but also a plurality of semiconductor chips in a state of being produced on one wafer.

It is evident from what has been explained above that  
30 the semiconductor device of the present invention is provided with low melting point metal ball bumps directly adhesive bonded to the respective electrodes formed on a semiconductor chip. The bumps can be made of high quality  
35 by making the size of the metal balls uniform. The metal balls are not formed on the electrodes of the semiconductor chip by a procedure such as plating or vapor

5

10

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

The present invention can be advantageously applied to flip chip bonding which makes possible high density mounting of a semiconductor device on a substrate.